Cavity Fixings



Delta-Drive, Brolly Anchors & Spring Toggles

Delta-Drive: Suitable for

Self drilling plasterboard fixing anchor. A one piece anchor that self drills into plasterboard, dry lined partition or acan i erated concrete. The point drills the hole, and the helical thread cuts into the board giving excellent locking properties to accept the fixing screw.

Application

Light weight items such as electrical boxes / light fittings, shelf brackets, mirrors, bathroom fittings etc. Comes complete with a 35mm, pan head self tapping screw.

Material & Sizes

High grade alloy.

One size Delta-drive to cover all applications.



Plasterboard, Fibreboard.

Application

Fixing in cavity situations where fire proofing is required. Also screw and anchor can be removed if so desired.

Material & Sizes

Manufactured from bright zinc plated steel with collapsing legs to create the anchor hold. Anti rotation lugs fitted to the anchor head. Setting tool available.

M4x 22mm to M6 x 53mm.

Spring Toggles: Suitable for

Plasterboard, Fibreboard, Lath walls/ceilings.

Application

Fixing in cavity situations where a load spread over a large area is required.

Material & Sizes

Manufactured from bright zinc plated steel with spring activated toggle bar.

M3 x 50mm to M6 x 75mm.

Packaging for all

In neutral packaging, (own label showing company name, code and bar code can be added).











Product Data: Delta-Drive



Product Data: Brolly Anchor

	Screw Length (mm)	Box Quantity	Outer Quantity	Drill Hole (mm)	Max Thickness of Base Material
M4 x 22mm	25	100	2000	7	0 - 5mm
M4 x 38mm	45	100	2000	7	8 - 16mm
M5 x 37mm	45	100	2000	8	6 - 13mm
M5 x 53mm	58	50	1000	8	3 - 16mm
M6 x 37mm	45	50	1000	10	6 - 16mm
M6 x 53mm	58	50	1000	10	3 - 16mm

Product Data: Spring Toggles

	Drill Hole (mm)	Max Thickness of Base Material	Box Quantity	Outer Quantity
M3 x 50mm	11	30mm	100	2400
M5 x 50mm	14	24mm	50	1200
M5 x 75mm	14	50mm	50	800
M5 x 100mm	14	72mm	25	600
M6 x 75mm	18	50mm	25	600